

TECHNICAL SPECIFICATIONS

Li-Ion Battery voltage	20 V
Li-Ion Battery capacity	2,0 Ah / 4,0 Ah
90 min battery charger	240 - 220 V / 50 - 60 Hz and 120 V 60 Hz
Maximum pressure	700 bar (10,000 psi)
Safety valve set pressure	500 bar (7,250 psi)
Flow rate - high	160 g/min (5.7 oz/min)
Flow rate - low	100 g/min (3.6 oz/min)
Grease cartridges per battery charge ⁽¹⁾	24 (2 Ah battery) - 40 (4 Ah battery)
Display functions	Battery level gauge, grease meter, grease level gauge, stall alarm, loss of prime alarm.
Measuring units	grams, ounces
LED flashlight	Yes, with on/off function
Hose length	1.100 mm (44")
Shoulder strap	Included
Grease gun weight	3,2 kg (7 lb)


⁽¹⁾ Low speed - low flow mode.

Number of 400 g grease cartridges per charge for 4.0 Ah grease gun through grease hose and grease coupler and grease fitting: 23 cartridges.

Number of 400 g grease cartridges per charge for 4.0 Ah grease gun through grease hose and grease coupler and no grease fitting: 36 cartridges.

Number of 400 g grease cartridges per charge for 4.0 Ah grease gun at free delivery, with no grease hose, grease coupler or grease fitting: 40 cartridges.

Number of 400 g grease cartridges per charge may vary depending on several factors, such as the battery charge, working pressure or grease viscosity.



ORDER INFORMATION

All models include one battery, battery charger, carrying case and one grease gun complete with delivery hose and grease coupler.

MODEL NUMBER

160 500	Battery grease gun with 1 x 2 Ah battery pack. 240 - 220 V / 50 - 60 Hz
160 500.300	Battery grease gun with 1 x 2 Ah battery pack. 110 V / 60 Hz
160 510	Battery grease gun with 1 x 4 Ah battery pack. 240 - 220 V / 50 - 60 Hz
160 510.300	Battery grease gun with 1 x 4 Ah battery pack. 110 V / 60 Hz

ACCESSORIES

169 503	Carrying case
169 012	Grease outlet hose
169 500	Battery charger
169 020	2 Ah - 20 V Lithium-Ion battery pack
169 021	4 Ah - 20 V Lithium-Ion battery pack



169 503



169 012



169 500



169 020 / 169 021

20 V Battery Grease Gun



SAMOA INDUSTRIAL, S. A. - HEADQUARTERS

SPAIN AND EXPORT MARKETS
POL. IND. PORCEYO, 1-14 - CAMINO DEL FONTÁN, 831
E-33392 GIJÓN (ASTURIAS), SPAIN
TEL.: +34 985 381 488 - FAX: + 34 985 147 213
export@samoaindustrial.com - www.samoaindustrial.com

SAMOA LTD.

UNITED KINGDOM AND REP. OF IRELAND
sales@samoaltd.uk - www.samoaltd.uk

SAMOA S.A.R.L.

FRANCE
samoafrench@samoafrench.com - www.samoafrench.com

SAMOA-HALLBAUER GMBH

GERMANY AND AUSTRIA
info@samoahallbauer.de - www.samoahallbauer.de

SAMSON CORPORATION

NORTH AMERICA
info@samsoncorporation.com - www.samsoncorporation.com

SAMOA CHINA SALES OFFICE

china@samoaindustrial.com



©Copyright, SAMOA INDUSTRIAL, S.A.

SAMOA Industrial, S.A. is an ISO 9001, ISO 14001 and ISO 45001 certified company.



20 V Battery Grease Gun

- 2 Ah or 4 Ah Lithium Ion battery
- Dual mode flow rate:
 - Low flow: 100 g/min (3.6 oz/min)
 - High flow: 160 g/min (5.7 oz/min)
- Up to 700 bar (10,000 psi) maximum pressure (limited to 500 bar - 7,250 psi with safety valve)
- Up to 40 grease cartridges per battery charge (see product technical specifications)

Multi-function LCD

LCD display provides real time critical information for keeping full control.

CE UK EAC

