220 I Equipped Tanks For Diesel AdBlue®/DEF Dispensing



DESCRIPTION

220 I tanks equipped with electric pumps and 4 m hose with automatic nozzle to ease refilling tasks. Their PE rotomolded manufacturing with extra reinforced wall thickness, make them very sturdy. Their engineered design, including lifting points for forklifts, give them improved manoeuvrability. Include several antispill leakage features such as safety filling cap and large lid with lockable latches. Supplied with made in EU HD 12 V DC electric pumps. They are conform to ADR 1.1.3.1 c/ exemption.

AVAILABLE PRODUCTS

Part No. 560 312

220 I AdBlue®/DEF tank with electric pump.

Part No. 684 516

220 I Diesel tank with electric pump.

TECHNICAL SPECIFICATIONS	
MAX. VOLUME	220 I (58 gallon)
WEIGHT (EMPTY)	24 kg (52 pound)
DELIVERY	AdBlue® version 30 l/min (8 gal/min)
	Diesel version 40 l/min (10.5 gal/min)
DELIVERY HOSE	Ø3/4" x 4 m / Ø3/4" x 13 feet
MATERIALS IN CONTACT WITH THE FLUID	AdBlue® version PA, PE, SS, Viton®, PP, EPDM, HNBR
	Diesel version PE, AL, NBR, Rubber, Cast iron

