## SANDA LEADING THROUGH INNOVATION

## 440 I Equipped Tanks For Diesel AdBlue<sup>®</sup>/DEF Dispensing



## DESCRIPTION


440 I tanks equipped with electric pumps and 4 m hose with automatic nozzle to ease refilling tasks. Their PE rotomolded manufacturing with extra reinforced wall thickness, make them very sturdy. Their engineered design, including lifting points for forklifts, give them improved manoeuvrability. Include several antispill leakage features such as safety filling cap and large lid with lockable latches and a dial level gauge. Supplied with made in EU HD 12 V DC electric pumps. They are conform to ADR 1.1.3.1 c/ exemption.

## **AVAILABLE PRODUCTS**

Part No. 560 313 440 I AdBlue<sup>®</sup>/DEF tank with electric pump.

Part No. 684 517 440 I Diesel tank with electric pump.

TECHNICAL SPECIFICATIONS	
MAX. VOLUME	440 l (116 gallon)
WEIGHT (EMPTY)	40 kg (88 pound)
DELIVERY	AdBlue® version 30 l/min (8 gal/min)
	Diesel version 40 l/min (10.5 gal/min)
DELIVERY HOSE	Ø3/4" x 4 m / Ø3/4" x 13 feet
MATERIALS IN CONTACT WITH THE FLUID	AdBlue® version PA, PE, SS, Viton®, PP, EPDM, HNBR
	Diesel version PE, AL, NBR, Rubber, Cast iron



В