1/2" Compact Enclosed Hose Reel

Aluminium enclosure with composite spool hose reels, can handle up to 15 m x 1/2" hose.

- · Totally enclosed reel in steel plate finished in polyester resin.
- Positionable mounting bracket in steel plate with 2 drill patterns: 220 x 130 mm and 270 x 150 mm.
- · Ratchet system in polymer to reduce noise.
- Large service panel allows hose reel maintenance without dismounting it.
- Wide hose outlet aids rolling, reduces piling up and premature wear of the hose.
- · Fatigue resistant steel spring for years of durable performance and even load when pulling and recoiling the hose.
- Spool mounted on two permanent lubricated and sealed ball bearings to reduce torque load on spring for smooth retraction and longer life.
- · Hose reels with hose include 0,8 m inlet hose.

MARKETS / APPLICATIONS · General manufacturing · Car and truck dealers · Service shops · Fleets Service stations · Lube trucks · Quick lubes **DIMENSIONS MM (INCHES)** 196,8 140 SAMOA **Fluids Handled** M h 5 LA. WATER Mounting Reel with arms in ceiling mounting position

Wall

Fino

Ceiling



RM-12CLX

REEL MASTER®

1/2" Compact Enclosed Hose Reel

PART No.	BARE REEL	HOSE IN O	HOSE LENGTH	CONNECTING HOSE INLET	OELIVERY HOSE OUTLET	PRESSURE RATING	WEIGHT (With hose)
			AIR /	WATER / ANTIFREEZE SOLUTI	ONS		
502 151	502 159	3/8"	10 m	3/8" BSP (M)	3/8" BSP (M)	15 bar	18,7 Kg
502 156	502 159	3/8"	15 m	3/8" BSP (M)	3/8" BSP (M)	15 bar	19,7 Kg
502 157	502 159	1/2"	15 m	1/2" BSP (M)	1/2" BSP (M)	15 bar	20,6 Kg
			WINDSHIELD WAS	H SOLUTIONS / DEF - AdBlue	/ DETERGENTS		
502 752	-	1/2"	10 m	1/2" BSP (M)	1/2" BSP (M)	20 bar	16,6 kg
502 757		1/2"	15 m	1/2" BSP (M)	1/2" BSP (M)	20 bar	16,6 kg
			S	YNTHETIC AND MINERAL OILS			
502 252	502 259	1/2"	10 m	1/2" BSP (M)	1/2" BSP (M)	160 bar	20.9 Kg
502 257	502 259	1/2"	15 m	1/2" BSP (M)	1/2" BSP (M)	160 bar	23 Kg
			GF	REASE AND HYDRAULIC FLUID	S		
502 350	502 359	1/4"	10 m	1/4" BSP(M)	1/4" BSP(M)	350 bar	20,4 Kg
502 351	502 359	3/8"	10 m	3/8" BSP(M)	1/4" BSP(M)	280 bar	21,9 Kg
502 356	502 359	3/8"	15 m	3/8" BSP(M)	1/4" BSP(M)	280 bar	24,45 Kg



